

MATERIAL SAFETY DATA SHEET

IMPORTANT NOTICE: This Material Safety Data Sheet (MSDS) is issued by ARTAV AUSTRALIA in accordance with Worksafe Australia guidelines. As such, the information contained herein must not be altered, deleted or added to. ARTAV AUSTRALIA will issue new MSDS should there be a change in product specifications and/or Worksafe guidelines/regulations. ARTAV AUSTRALIA will not accept responsibility for any changes made to its MSDS in content by any other person or organisation.

Section 1 CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: Artists Selection Cosmetics Professional Makeup Brush Cleaner
SYNONYMS: Brush Cleaner
PRODUCTTYPE: Makeup Brush Cleaner
PRODUCT USE: Cleaner for make-up brushes
PRODUCT SUPPLIER: Crown Brush
Unit 1 / 9 Central Drive
Burleigh Heads
Queensland, 4220
Tel: +61 7 5593 7757
crownbrush.com.au

Section 2 HAZARDS IDENTIFICATION

This product is flammable

STATEMENT OF HAZARDOUS NATURE

Hazardous substance, dangerous goods according to the criteria of NOSHC

POISONS SCHEDULE: Not applicable

Hazard category: refer Section 15

RISK

Flammable material
Irritant to the skin on prolonged contact
Irritant to the eyes
Slippery when wet

SAFETY

Avoid all sources of ignition
Avoid prolonged contact with the skin
Avoid eye contact.
Clean-up spills
Store in a cool dry area

Aqueous solution of isopropanol

Risk phrase

R66 Repeated exposure to the skin may cause skin drying and cracking

Safety phrase

S16 Keep away from sources of ignition. No smoking

S23 Do not breathe the vapour

S7/9 Keep container tightly closed and in a well ventilated place

Section 3 COMPOSITION

HAZARDOUS INGREDIENTS:

Isopropanol	CAS 67-63-0	> 60%
-------------	-------------	-------

OTHER INGREDIENTS: Non hazardous ingredients to 100%

Section 4 FIRST AID MEASURES

SWALLOWED: Rinse mouth with water. Give water to drink. DO NOT induce vomiting

Seek immediate medical assistance.

Contact Doctor or Poisons Information Centre

EYES: Remove contact lenses. Irrigate 15 minutes with cold water, including under eyelids. If discomfort persists seek medical attention promptly.

SKIN: Wash with soap and water. Seek medical attention if irritation develops.
Remove contaminated clothing. If redness or swelling persists, seek medical attention

INHALED: If symptoms of over exposure are experienced, remove to fresh air.
Lay person down. Keep warm and rested
Prostheses such as false teeth which may block airways should be removed prior to commencing first aid

ADVICE TO DOCTORS (Emergency Treatment) : Treat symptomatically

Section 5 FIRE FIGHTING MEASURES

Specific Hazards: Flammable liquid. Avoid all ignition sources.

Fire fighting further advice: Flammable liquid. Heating can cause rupture of containers.
Keep containers cool with water spray. Burning will result in the release of toxic fumes, including carbon dioxide. Fire fighters are to wear self-contained breathing apparatus if the extent of the fire reduces access to fresh air.

Suitable extinguishing media: Foam, dry chemical, carbon dioxide.

Fire/Explosion Hazards: Combustible liquid
Alert Fire Brigade and advise nature of the chemical substance
Wear self contained breathing apparatus in the event of major fires
Do not approach containers that may be hot
Combustion will result in the release of large quantities of carbon dioxide, carbon monoxide and .
oxides of nitrogen
Burns with a sooty flame

Fire incompatibility:
Avoid contact with oxidising agents

Hazchem Hazchem code: not assigned

Section 6 ACCIDENTAL RELEASE MEASURES

Minor Spills:
Clean up all spills promptly. Avoid breathing vapours. Place in suitable containers for disposal.
May be a slip hazard.

Major Spills:
Clear personnel not involved with clean-up from the work area
Shut off all sources of ignition. Do not smoke. Increase ventilation. Spread sand to reduce slip hazard. Clean spills immediately.
Wear self protective equipment to eliminate contact and inhalation of vapours.
Collect and seal in metal containers for subsequent safe disposal according to the requirement of local government.
If contamination of sewers or waterways occurs, immediately notify the relevant authorities.

STEL (Short term Exposure limit)- the average airborne concentration over a 15 minute period which should not be exceeded.

Section 7 HANDLING AND STORAGE

Precautions as for combustible liquids. Avoid contact with polymerisation catalysts such as Aluminium chloride and acidic clays. Avoid strong oxidising agents.
Store in a cool place out of direct sunlight, and away from all potential sources of ignition.
Keep containers closed when not in use.
Suitable container; PET plastic container

Section 8 EXPOSURE CONTROLS

National occupational exposure limits: No value assigned

Exposure

The maximum airborne concentration below which it is believed most individuals may work without ill effects is as follows:

Isopropanol

TWA- 400ppm (983mg/m3)
STEL- 500ppm (1230mg/m3)
Carcinogen category- none allocated

Exposure standard (TWA) is the time weighted average air borne concentration over an eight hour working day for a five day working week over an entire working life

STEL (Short term Exposure limit)- the average airborne concentration over a 15 minute period which should not be exceeded.

Engineering measures: use in a well ventilated area. Keep containers closed when not in use.

Personal protective measures: Not required when used in accordance with the directions supplied. In the case of accidental spills, wear gloves and safety goggles.

Gloves should be neoprene, PVC or butyl.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear liquid
BOILING/MELTING POINT:	not determined
VAPOUR PRESSURE:	not determined
FLASH POINT:	12°C (Isopropanol)
FLAMMABILITY LIMITS:	not determined
DENSITY:	not determined
SOLUBILITY IN WATER:	soluble
VOLATILES:	isopropanol and water
AUTOIGNITION:	not determined

Section 10: STABILITY AND REACTIVITY

Chemical stability:	Stable
Hazardous polymerisation:	Stable
Conditions to avoid:	Heat, flame, sparks, static charge
Incompatible materials:	Incompatible with oxidising agents, acidic clays and mineral acids
Hazardous decomposition products:	carbon dioxide, carbon monoxide.

Section 11: TOXICOLOGICAL INFORMATION

SWALLOWED: May result in nausea, vomiting and abdominal pain

EYES: Moderate to high eye irritant

SKIN: Repeated or prolonged skin contact may cause irritation.
Some individuals may be sensitised and experience more than normal skin reaction.
Intensive skin contact may result in defatting of the skin and may result in dermatitis.

INHALED: Inhalation can cause nose, throat and respiratory tract irritation, coughing and headache.

LONG TERM: Prolonged or repeated exposure may lead to drying, defatting or dermatitis of the skin

LONG TERM EFFECTS: Prolonged exposure may lead to defatting of the skin
Acute toxicity/chronic toxicity

Isopropanol is a major component of Brush Cleaner. This has an exposure limit of
Oral LD50 (rat): 4396mg/kg

Section 12: ECOLOGICAL INFORMATION

Avoid contaminating waterways. Not a marine pollutant.

Section 13: DISPOSAL CONSIDERATIONS

Refer to the relevant local authorities for disposal procedures. Advise flammable nature.

Section 14: TRANSPORT INFORMATION

Classified as Dangerous Goods for the purpose of transport by road or rail.

Refer to relevant local regulations for storage and transport

CLASS: 3 Flammable liquid

UN No: 1219

Class 3 Flammable Liquid

Packaging Group: 11

Shipping name: Isopropanol

Segregation: Not to be loaded with explosives Class 1, flammable gases Class 2.1, spontaneously combustible material Class 4.2, oxidising agents Class 5.1, organic peroxides Class 5.2 or radioactive substances Class 7.

Section 15: REGULATORY INFORMATION

Hazardous substance according to the requirements of Worksafe Australia

Section 15: OTHER INFORMATION:

Disposal of cloths containing Dissolve with rubbish may constitute a fire hazard. Dispose of in water or allow Dissolve to completely evaporate.

* * **CONTACT POINT:** CROWN BRUSH +61 7 5593 7757

DATE: 22.07.24

Issue Number : 1

Discard this MSDS and seek a replacement by: 22/07/2026

NOTE: The information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation. However no responsibility can be accepted by ARTAV AUSTRALIA, its parent, related and subsidiary companies for errors and omissions. The providing of this information should not be interpreted as a recommendation to use this product in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determinations as to the suitability of this information for their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by ARTAV AUSTRALIA, its parent, related and subsidiary companies for any loss or damage caused by any person acting, or refraining from action, as a result of this information.